

外壁用ステンレス製換気口〈フラットグリル〉

Stainless Steel VentCaps

CX-S



〈ガラリ型〉



- 材質 SUS304
- 仕上 シルバー焼付塗装


●金網付型式

CX-SN 10M
CX-SN 5M
CX-SN 3M



圧力損失特性

圧力損失係数	流量係数(開口率)	有効開口面積 (cm ²)
2.27	66.4%	52.1
1.67	77.4%	94.9
3.19	56.0%	98.9
1.71	76.5%	184
3.15	56.3%	176.9



Dimensions

*指定色は日塗工の番号でご指定下さい。

Model	A	B	C	D	標準価格	金網加算	指定色加算
CX 65S	62	112	10	42	¥1,900	¥400	¥1,100
CX 75S	72	112	10	42	¥1,900	¥400	¥1,100
CX100S	97	135	10	47	¥2,100	¥500	¥1,200
CX125S	122	159	10	52	¥3,000	¥600	¥1,400
CX150S	147	183	10	52	¥3,200	¥700	¥1,500
CX175S	170	209	10	67	¥5,200	¥800	¥1,700
CX200S	197	234	10	77	¥5,500	¥900	¥1,900

CXD-S



〈ガラリ型 防火ダンパー付〉



- 材質 フェイス:SUS304
FD:鋼板 1.6t
- 仕上 シルバー焼付塗装
- 温度フューズ 標準72℃
オプション 120℃・180℃


●金網付型式

CXD-SN 10M
CXD-SN 5M
CXD-SN 3M



圧力損失特性

圧力損失係数	流量係数(開口率)	有効開口面積 (cm ²)
2.8	59.8%	46.9
2.2	67.4%	82.7
3.51	53.4%	94.3
3.33	54.8%	172.2



Dimensions

*指定色は日塗工の番号でご指定下さい。

Model	A	B	C	D	標準価格	金網加算	指定色加算
CXD100S	97	135	10	47	¥5,000	¥500	¥1,200
CXD125S	122	159	10	52	¥6,500	¥600	¥1,400
CXD150S	146	183	10	47	¥6,100	¥700	¥1,500
CXD200S	197	234	10	62	¥9,400	¥900	¥1,900

CXD-SC



〈ガラリ型 防火ダンパー付〉



- 材質 フェイス:SUS304
FD:SUS304 1.5t
- 仕上 シルバー焼付塗装
- フェイス脱着式
- 温度フューズ 標準72℃
オプション 120℃・180℃


●金網付型式

CXD-SCN 10M
CXD-SCN 5M
CXD-SCN 3M



圧力損失特性

圧力損失係数	流量係数(開口率)	有効開口面積 (cm ²)
3.37	54.5%	42.8
2.41	64.4%	78.9
3.69	52.1%	92
2.02	70.4%	169.3
3.53	53.2%	167.1



Dimensions

*指定色は日塗工の番号でご指定下さい。

Model	A	B	C	D	標準価格	金網加算	指定色加算
CXD 75SC	72	112	10	52	¥4,000	¥400	¥1,100
CXD100SC	97	135	10	67	¥4,600	¥500	¥1,200
CXD125SC	122	159	10	83	¥6,100	¥600	¥1,400
CXD150SC	147	183	10	97	¥6,800	¥700	¥1,500
CXD175SC	172	209	10	107	¥9,800	¥800	¥1,800
CXD200SC	197	234	10	117	¥11,100	¥900	¥2,000