

SIZE	Nozzle Area	Nozzle Velocity (fpm)	400	600	800	1000	1200	1400	1600	1800	2000
PK8K	Ø2.99in 0.0484sq.ft	CFM	27	41	56	71	85	100	115	130	144
		Ps	0.01	0.02	0.04	0.06	0.10	0.13	0.17	0.22	0.27
		Throw (Vt=@100fpm)	5	8	10	12	15	18	20	23	26
		Throw (Vt=@50fpm)	8	12	16	20	24	29	33	37	41
		NC	-	-	-	-	21.2	27.5	32.7	37.1	40.8
PK10K	Ø4.528in 0.112sq.ft	CFM	59	89	118	148	177	207	236	266	295
		Ps	0.01	0.02	0.04	0.06	0.09	0.12	0.16	0.20	0.25
		Throw (Vt=@100fpm)	7	11	15	18	22	26	31	34	39
		Throw (Vt=@50fpm)	12	17	24	30	36	42	48	55	62
		NC	-	-	-	-	19.3	25.0	30.3	34.4	37.9
PK12K	Ø5.315in 0.154sq.ft	CFM	77	118	159	200	241	283	324	365	406
		Ps	0.01	0.02	0.04	0.06	0.09	0.12	0.16	0.21	0.26
		Throw (Vt=@100fpm)	9	13	17	22	26	31	36	40	45
		Throw (Vt=@50fpm)	14	20	27	35	41	49	57	64	72
		NC	-	-	-	-	19.5	24.9	30.2	34.3	38.1
PK12WK	Ø6.102in 0.203sq.ft	CFM	100	153	206	259	312	365	418	471	524
		Ps	0.01	0.02	0.04	0.06	0.09	0.12	0.16	0.20	0.25
		Throw (Vt=@100fpm)	10	15	20	25	30	36	41	46	51
		Throw (Vt=@50fpm)	16	24	32	40	48	57	66	74	82
		NC	-	-	-	-	21.3	27.4	32.3	36.0	39.1
PK16K	Ø7.32in 0.292sq.ft	CFM	153	236	318	401	483	565	648	730	813
		Ps	0.01	0.02	0.03	0.05	0.08	0.11	0.14	0.18	0.22
		Throw (Vt=@100fpm)	11	17	22	28	33	40	46	51	56
		Throw (Vt=@50fpm)	18	28	36	45	54	64	73	82	91
		NC	-	-	-	18.2	25.4	31.6	36.1	39.9	43.4

DASHED LINE IN NC BOX INDICATES NOISE LEVEL IS LESS THAN 17.

*Seiho International reserves the right to make changes without prior notice.

*This performance data is proprietary to Seiho International, Inc., and shall not be used except as expressly authorized by the Company.