

外壁用ステンレス製換気口〈ベントキャップ〉

SV-GS 〈薄型〉



材質

フェイス：SUS304
胴体：SUS304

仕上

シルバー焼付塗装



SV-GSN 10M
SV-GSN 5M
SV-GSN 3M

(金網付はビス止めとなります)

Dimensions

※指定色は日塗工の番号でご指定下さい。


Model	A	B	C	D	標準価格	金網加算	指定色加算	低圧損
SV50GS	47	110	88	46	¥2,200	¥500	¥1,400	
SV65GS	62	110	88	46	¥2,200	¥500	¥1,400	
SV75GS	72	110	88	46	¥2,200	¥500	¥1,400	○
SV100GS	97	137	115	46	¥2,600	¥600	¥1,500	○
SV125GS	122	164	140	46	¥3,300	¥700	¥1,800	○
SV150GS	147	190	165	51	¥3,700	¥1,200	¥1,900	○
SV175GS	170	213	189	56	¥4,800	¥1,700	¥2,100	○
SV200GS	197	237	212	71	¥5,500	¥2,100	¥2,400	

2 管路製品

Model	A	B	C	D	標準価格	金網加算	指定色加算
SVK125GS-VP	122	164	140	46	¥3,600	¥700	¥1,800
SVK125GS-VM	128	164	140	46	¥3,600	¥700	¥1,800

圧力損失特性

サイズ	圧力損失係数		有効開口面積 (cm ²)
	排気	開口率	
75	0.85	108.5%	47.8
100	1.09	95.8%	75.2
125	0.96	102.1%	125.3
150	1.06	97.1%	171.7
175	1.18	92.1%	221.8
200	1.55	80.3%	252.1



SV-GS 大口徑 〈薄型〉



材質

フェイス：SUS304
胴体：SUS304

仕上

シルバー焼付塗装



SV-GSN 10M
SV-GSN 5M
SV-GSN 3M

(金網付はビス止めとなります)




Dimensions

※指定色は日塗工の番号でご指定下さい。

Model	A	B	C	D	標準価格	金網加算	指定色加算	低圧損
SV225GS	220	257	232	71	¥12,500	¥2,500	¥3,200	
SV250GS	245	316	286	71	¥14,000	¥3,000	¥3,400	○
SV300GS	295	377	345	71	¥20,000	¥4,000	¥4,300	

圧力損失特性

サイズ	圧力損失係数		有効開口面積 (cm ²)
	排気	開口率	
225	2.3	65.9%	262.2
250	1.08	96.2%	471.2
300	2.52	63.0%	445



SVD-GS <薄型 防火ダンパー付>





材質 フェイス: SUS304
FD: 銅板 1.6t

仕上 シルバー焼付塗装

温度フェース 標準72°C
オプション120°C・180°C

金網付型式

SVD-GSN 10M
SVD-GSN 5M (金網付はビス止め
となります)
SVD-GSN 3M




Dimensions

※指定色は日塗工の番号でご指定下さい。

Model	A	B	C	D	標準価格	金網加算	指定色加算
SVD100GS	97	137	115	42	¥6,000	¥600	¥1,500
SVD125GS	122	164	140	47	¥8,600	¥700	¥1,800
SVD150GS	146	190	165	42	¥7,600	¥1,200	¥1,900
SVD200GS	197	237	212	57	¥12,300	¥2,100	¥2,400

圧力損失特性

サイズ	圧力損失係数	流量係数	有効開口
	排气	開口率	面積 (cm ²)
100	1.74	75.8%	59.5
125	1.37	85.4%	104.8
150	1.51	81.4%	143.6
200	1.59	79.3%	249.3



SVD-GSC <薄型 防火ダンパー付>



材質 フェイス: SUS304
FD: SUS304 1.5t



仕上 シルバー焼付塗装

フェイス着脱式

温度フェース 標準72°C
オプション120°C・180°C

金網付型式

SVD-GSCN 10M
SVD-GSCN 5M
SVD-GSCN 3M




Dimensions

※指定色は日塗工の番号でご指定下さい。

Model	A	B	C	D	標準価格	金網加算	指定色加算
SVD75GSC	72	110	88	47	¥5,100	¥500	¥1,400
SVD100GSC	97	137	115	62	¥5,700	¥600	¥1,500
SVD125GSC	122	164	140	78	¥7,400	¥700	¥1,800
SVD150GSC	147	190	165	92	¥7,800	¥1,200	¥1,900
SVD175GSC	172	213	189	102	¥11,000	¥1,700	¥2,100
SVD200GSC	197	237	212	112	¥12,000	¥2,100	¥2,400

圧力損失特性

サイズ	圧力損失係数	流量係数	有効開口
	排气	開口率	面積 (cm ²)
100	1.96	71.4%	56
125	1.87	73.1%	89.7
150	1.64	78.1%	137.8
175	1.56	80.1%	192.5
200	1.74	75.8%	238.2



SVD-GSC 大口徑 <薄型 防火ダンパー付>



材質 フェイス: SUS304
FD: SUS304 1.5t



仕上 シルバー焼付塗装

フェイス着脱式

温度フェース 標準72°C
オプション120°C・180°C

金網付型式

SVD-GSCN 10M
SVD-GSCN 5M
SVD-GSCN 3M



Dimensions

※指定色は日塗工の番号でご指定下さい。

Model	A	B	C	D	標準価格	金網加算	指定色加算
SVD250GSC	247	316	286	140	¥28,800	¥3,000	¥3,400

圧力損失特性

サイズ	圧力損失係数	流量係数	有効開口
	排气	開口率	面積 (cm ²)
250	1.57	79.8%	391.6

