BL 製品

ST-FSBL · STD-FSCBL

ST-FSBL 〈厚型 縦ガラリ 低圧損〉











材質

フェイス :SUS304 胴体 :SUS304

仕 上

シルバー焼付塗装

公団呼称

vsus

BL 認定番号

BLVU040510




| Dimensions - | ensions — ※指定色は日塗工の番号でご指定下 | | | | | | ご指定下さい。 |
|--------------|----------------------------|-----|-----|----|--------|--------|---------|
| Model | Α | В | С | D | 標準価格 | 金網加算 | 指定色加算 |
| ST100FSBL | 97 | 137 | 115 | 46 | ¥2,600 | ¥600 | ¥1,500 |
| ST125FSBL | 122 | 164 | 140 | 46 | ¥3,500 | ¥700 | ¥1,800 |
| ST150FSBL | 147 | 190 | 165 | 51 | ¥4,000 | ¥1,200 | ¥1,900 |


2 管路製品


| Model | Α | В | С | D | 標準価格 | 金網加算 | 指定色加算 |
|---------------|-----|-----|-----|----|--------|------|--------|
| STK125FSBL-VP | 122 | 164 | 140 | 46 | ¥3,800 | ¥700 | ¥1,800 |
| STK125FSBL-VM | 128 | 164 | 140 | 46 | ¥3,800 | ¥700 | ¥1,800 |



ST-FSNBL 10M ST-FSNBL 5M ST-FSNBL 3M







STD-FSCBL 〈厚型 縦ガラリ 防火ダンパー付 低圧損〉











9



材

フェイス:SUS304 FD:SUS304 1.5t

仕 上

シルバー焼付塗装

温度フューズ

標準 72℃


オプション 120℃

公団呼称

VSUSD

BL 認定番号

BLVU040510



| | ※指定巴は日空工の番号でご指定下さい | | | | | | し指定下さい。 |
|-------------|--------------------|-----|-----|----|--------|--------|---------|
| Model | Α | В | С | D | 標準価格 | 金網加算 | 指定色加算 |
| STD100FSCBL | 97 | 137 | 115 | 62 | ¥5,600 | ¥600 | ¥1,500 |
| STD125FSCBL | 122 | 164 | 140 | 78 | ¥7,400 | ¥700 | ¥1,800 |
| STD150FSCBL | 147 | 190 | 165 | 92 | ¥7,900 | ¥1,200 | ¥1,900 |

金網付型式

STD-FSCNBL 10M STD-FSCNBL 5M STD-FSCNBL 3M

圧力損失特性

